

WAGNER

**SuperFinish
Crack Injection**



NEW

SuperFinish SF23 Pro i & SF33 Pro i **PROFESSIONAL CRACK INJECTION**

- Precise, user-friendly and efficient in filling and redevelopment
- QLS - Quality Long Stroke diaphragm pump ideal for both high and low viscosity materials
- Suitable for a range of materials: epoxy, polyurethane (PU), SPUR foam and aqueous solutions

www.wagneraustralia.com.au



Foldable handle

Folds down for easy storage and transport.

Innovative QLS technology

Quality Long Stroke with optimised hydraulics for high performance & longer service life.

Brushless motor

Requires no maintenance.

Precise Injection

Easy to use with all packings commercially available.

HEA Pressure Gauge

Infinitely variable pressure regulation from 0 to 3600 PSI.

5 litre hopper

*20 litre hopper available as an additional accessory
**SF33 Pro comes with flexible suction system

Thermal overload protection

On/Off switch contains a thermal overload, which protects the electric motor in the event of low voltage supply.




SPARE PARTS AVAILABLE

	Part No.
Inlet Valve Cartridge (01)	2393043
Outlet Valve Cartridge (02)	2342946
Injection Lance Ball Valve (03)	04348
Injection Lance (bare) (04)	700-100
Connecting Nipple (05)	0034031L
SF33 Inlet Valve	0341254
SF33 Outlet Valve	0341702



THE BENEFITS OF DIAPHRAGM PUMP TECHNOLOGY

Diaphragm pumps are a great choice when it comes to handling a wide variety of materials, from thin liquids to high-viscosity paints. QLS technology and low stroke frequency puts less stress on the components, significantly extending the service life of the pump and reducing maintenance costs. Valves are made of wear-resistant carbide and the diaphragm is made of solvent resistant polyamide.



INCLUSIONS

- SF23 Pro or SF33 Pro
- 15m airless hose
- 5 litre hopper (SF23 Pro) | 20 litre hopper (SF33 Pro)
- HEA pressure gauge
- Injection Lance with ball valve
- Tool bag; incl. wrench 41mm/22mm/19mm and screw driver

TECHNICAL DATA

	SF23 Pro i	SF33 Pro i
Part Number:	2395486i	2409323i
Motor Rating:	1.3 kW	2.2 kW
Lance Included:	Injection Lance Complete	Injection Lance Complete
Hose Length:	15 m	15 m
Max. Operating Pressure:	3600 psi	3600 psi
Max. Flow Rate:	2.6 l/min	4.31 l/min
Weight:	27 kg	43 kg

